ITTEST

QUESTION & ANSWER

Guías de estudio precisos, Alta tasa de paso!

Ittest ofrece información actualizada de forma gratuita en un año!

http://www.ittest.es/

Exam : **000-150**

Title : IBM J2EE 1.4 Web
Developer

Version : DEMO

1. Which two of the following BEST describes the behavior of the Web container in a distributed HTTP session management environment?

A. It must call the readObject() and writeObject() methods of a serialized object when the session is passivated.

B. It must call the methods in the HttpSessionActivationListener interface in the case of session migration.

C. It must preserve session state when the session is passivated.

D. It must store the state of static variables when the session is passivated.
Answer: BC

2. A developer wants to measure how many times a servlet has been invoked. Which listener could be used to accomplish this task?

A. HttpSessionListener

B. ServletContextListener

C. ServletRequestListener

D. ServletRequestAttributeListener
Answer: C

3. A client has accessed a servlet via a form that uses an HTTP POST request. Which two methods could be used by the servlet to obtain information input within the form?

A. Using the servlet object's getServletInfo() method

B. Using the request object's getAttribute() method

C. Using the request object's getParameter() method

D. Using the request object's getParameterValues() method

E. Using the request object's getAttributeValues() method
Answer: CD

4. If a server has URL rewriting enabled, what is the result of using the encodeURL() method of the HttpResponse interface?

A. Encryption of sensitive client data in the URL

B. Increased performance due to browser specific information being encoded in the URL

C. Redirection of all subsequent requests to a unique domain specified as a URL parameter

D. Addition of a client's session ID to the URL in a query string
Answer: D

5. In a travel booking Web application, a servlet uses JAX-RPC to call a Web service to alter the date on an airline ticket. The Web service throws an exception indicating it cannot change the flight because no seats are available on the requested new date. How does the servlet know that the request was not successful?

A. The servlet receives a SOAP message that contains a fault element.

B. The servlet receives a SOAP message that contains an empty body.

C. The servlet catches a java.rmi.RemoteException or a service-specific exception.

D. The servlet catches a javax.xml.rpc.JAXRPCException.
Answer: C

6. In a Web application that is layered in accordance with the MVC design pattern, which object or layer of code is responsible for deciding whether the user request should be accepted given the current state of the application?

A. JavaScript within the HTML page that submits the request

B. The servlet that receives the request

C. The transaction manager object that ensures consistency of persistent data

D. The core business logic of the application
Answer: B

7. In a standard JavaServer Faces page request processing life cycle, which two of the following phases must be executed no matter what kind of request is received?

A. Restore View

B. Invoke Application

C. Process Validation

D. Render Response

Answer: AD

8. Which method will cause the session to be automatically invalidated if it is not used during a specified time interval?

A. setTimeOutInterval()

B. setInactiveTimeOutInterval() C. setInvalidateInterval()

D. setMaxInactiveInterval()
Answer: D

9. Which method in the ServletContext interface could be used to get the value of a variable named times_Accessed ?

A. getAttribute("times_Accessed")

B. getAttributeValue("times_Accessed")

C. getParameter("times_Accessed")

D. getParameterValue("times_Accessed")
Answer: A

10. Which of the following would be legal parameters for the include() method of the RequestDispatcher object?

A. ServletHttpRequest, ServletHttpResponse

B. HttpServletReq, HttpServletResp

C. ServletRequest, ServletResponse

D. ServletReq, ServletResp
Answer: C