



## **QUESTION & ANSWER**

Guías de estudio precisos, Alta tasa de paso!



Ittest ofrece información actualizada de forma gratuita en un año!

http://www.ittest.es/

## Exam : 210-010

# Title: VCE Vblock™ SystemsDeployment andImplementation - Core Exam

### Version : DEMO

- 1. When powering on a Vblock System what is the correct power up sequence?
- A. Switches, AMP, SAN, UCS chassis, and UCS blades
- B. Switches, SAN, UCS chassis, UCS blades, and AMP
- C. Switches, AMP, UCS chassis, UCS blades, and SAN
- D. Switches, SAN, AMP, UCS chassis, and UCS blades

#### Answer: A

- 2.What are three primary site survey considerations? (Choose three.)
- A. Site information
- B. Technical resources
- C. Customer power requirements
- D. Data center physical audit
- E. Disaster recovery plan

Answer: A,C,D

3. Which EMC software is required to initialize a Vblock System 200 storage array?

- A. Unisphere Service Manager
- B. Unisphere Server Utility
- C. VNX Installation Assistant
- D. Unisphere Client

#### Answer: C

4. Which EMC software is required to upgrade code on a Vblock System 200 storage array?

- A. Unisphere Service Manager
- B. Unisphere Server Utility
- C. VNX Installation Assistant
- D. Unisphere Client
- Answer: A

5. Which two statements are correct about Vblock System Release Certification Matrix (RCM) upgrades? (Choose two.)

- A. The RCM must be applied by VCE certified resources.
- B. When upgrading to a new RCM, all components may not require an upgrade.
- C. The most recent RCM version must be applied.
- D. An addendum to the RCM may be issued to address a bug or software issue.

#### Answer: B,D

6. Which Cisco Catalyst switch is used for network management on a Vblock System 200?

- A. Cisco Catalyst 2960
- B. Cisco Catalyst 3560
- C. Cisco Catalyst 3750
- D. Cisco Catalyst 4500

#### Answer: C

7.In addition to the Logical Configuration Survey (LCS), which document is required prior to manufacturing a Vblock System 720?

- A. Configuration Reference Guide
- B. VCE change control form
- C. VCE Vblock Systems Release Certification Matrix
- D. EMC bin file request form

#### Answer: D

8.For bare metal deployments, which statement ensures VCE is able to provide reasonable-effort support?

- A. The ratio of bare metal to virtualized hosts cannot be more than 40 percent.
- B. A minimum of five virtualized hosts must be enabled.
- C. Bare metal workloads are run on separate physical spindles, disk groups, and pools.
- D. Systems cannot include hypervisor technologies other than VMware.

#### Answer: C

9.Customers provide the information used to develop the Logical Configuration Survey (LCS) before manufacturing begins.

What information is required? (Choose two.)

- A. syslog server IP address
- B. NTP server IP address
- C. method of device access (telnet or SSH)
- D. MIB browser IP address

#### Answer: B,C

10. The implementation profile located in the Logical Configuration Survey (LCS) identifies if the customer will be using which two solutions? (Choose two.)

- A. EMC SnapView
- B. Cisco IAC
- C. Cisco Unified Communications
- D. VMware vCloud Director

Answer: C,D

- 11.What are three requirements of the Vblock System test plan? (Choose three.)
- A. All tests identified in the test plan must be executed.
- B. Observed results must be documented by a VCE certified resource.
- C. Tests are confidential and must not be performed in view of the customer.
- D. Once tests are completed, the customer must sign the test plan document.
- E. A completed test plan must be submitted to the VCE project manager.

Answer: B,D,E

12. Which test is only performed on a Vblock System 320 that contains a high availability Advanced Management Pod (HA-AMP)?

A. Cisco blade server failure test

- B. Cisco UCS single power supply failure test
- C. Cisco Catalyst 3560 failure and recovery test
- D. Cisco UCS C220 failover test

#### Answer: D

13. Your manager asks you to configure an external Syslog on VMware ESXi hosts.

- In which two ways would the Syslog be configured? (Choose two.)
- A. using the vSphere client
- B. using the esxcli system syslog command
- C. using VMware Update Manager
- D. using the VMware SQL database

Answer: A,B

14. When performing hardware maintenance on a Cisco UCS B-Series blade, which GUI parameter should be selected before removing the blade out of the chassis?

- A. Remove
- B. Re-acknowledge
- C. Decommission
- D. Diagnostic Interrupt

#### Answer: C

15.A customer notices a failed drive error for a Vblock System 320 storage array on an EMC Unisphere screen.

Which logs must be collected and sent to VCE support to confirm that the drive has failed?

- A. SPcollects
- B. NAR files
- C. symapi.log
- D. EMC Grab

Answer: A

16.A customer wants to ensure that the new installed Vblock System 320 storage array is being monitored by EMC.

Which EMC monitoring tool must be installed to accomplish this?

- A. Data Center Network Manager (DCNM)
- B. EMC Secure Remote Support (ESRS)
- C. EMC OnAlert
- D. ConnectEMC
- Answer: B

17.Which two steps are required to complete a Cisco UCS Smart Call Home registration on a Vblock System? (Choose two.)

A. After receiving the e-mail response from Cisco, click the link in the e-mail to complete registration for Smart Call Home.

B. Select "Send System Inventory Now" in UCSM.

C. Configure UCSM to send periodic system inventory messages.

D. Configure the SNMP trap destination.

#### Answer: A,B

18. Which port is used for communication between EMC Secure Remote Support (ESRS) and the Policy Manager?

- A. 443
- B. 5414
- C. 8090
- D. 8443

#### Answer: D

19.You are backing up a Cisco UCS configuration.

Which parameter should you select to retain assigned vHBAs, WWPNs, vNICs MACs, WWNNs, and UUIDs?

- A. Retain Identities
- B. Preserve Identities
- C. Include Identities
- D. Copy Identities

Answer: B

20. Which Cisco management software is required to setup EMC e-mail home for Cisco MDS switches?

- A. Cisco Data Center Network Manager (Cisco DCNM-SAN)
- B. Cisco Unified Computing System Manager (Cisco UCSM)
- C. Cisco Smart Call Home (Cisco SCH)
- D. Cisco Terminal Access Controller Access Control System (Cisco TACACS)

Answer: A