

ITTEST

QUESTION & ANSWER

Guías de estudio precisos, Alta tasa de paso!



Ittest ofrece información actualizada de forma gratuita en un año!

Exam : 920-537

Title : CVoIP MG 15K Operations,

Maintenance &

Configuration

Version: DEMO

1. Which group of four network management interfaces is used to access a Multiservice Switch 15000?
A. IP, telnet, FMIP, local
B. local, NMS, IP, FMIP
C. datastream, telnet, local, FMIP
D. local, telnet (remote), FMIP, FTP
Answer: D
2. Which network management interface is exclusively for MDM workstation access with the Multiservice
Switch 15000?
A. FTP
B. FMIP
C. Local
D. Telnet
Answer: B
3. How many simultaneous telnet sessions can be active at one time?
A. 1
B. 8
C. 16
D. 35
Answer: C
4. Click the exhibit button
Which of the following attributes of the software download (Sw Dld) component needs to be configured
prior to initiating the download command?

- A. filesToTransfer
- B. downloadedAvList
- C. avListToDownload
- D. avBeingDownloaded

Answer: C

- 5. Which command will display all software that could be removed (erased) from the Multiservice Switch 15000 disk file system?
- A. tidy sw
- B. tidy -q sw
- C. tidy -all prov
- D. remove Sw AV/named_version

Answer: B

- 6. Which command is used to show all the software applications on the hard drive of a Multiservice Switch 15000?
- A. d sw av
- B. d-psw

- C. d sw avl
- D. I sw av/*

Answer: D

- 7. What is the component name that represents an instance of a Media Gateway 15000?
- A. Logical Processor (LP)
- B. TDM Access Group (TAG)
- C. Basic Rate Access Group Server (BRAGS)
- D. Narrowband Services Trunk over ATM (NSTA)

Answer: D

8. Click the exhibit button.

What network element does the IP Address and UDP Port number as shown by operational attribute mgcMid identify?

```
Select Telnet 47.140.92.161
                                                                                                  _ 0
7> d nsta/14 vgs h248/0
Nsta/14 Ugs H248/0
   negotiatedVersion = 1
                           = 2112
   maximumContexts
   normalMgExecutionTime = 500 msec
normalMgcExecutionTime = 500 msec
   mgProvisionalRespTimerValue = 2000 msec
   mgcProvisionalRespTimerValue
maximumInactivityTime
                                        = 500 msec
                                           12000 msec
   failovers
                                           [172.17.87.148]:2944
   mgcMid
                                           172.17.87.148
2944
   mgcAddress
   mgcPort
   mgcInUse
                                           Nsta/14 Ugs Mgc/0
   txRetransmissions
   rxRetransmissions = 0
2007-07-30 14:28:59.68
```

- A. Gateway Controller (GWC)
- B. CS2000 Management Tool (CMT)
- C. Media Gateway 15000 (MG 15000)
- D. Communication Server (CS2000/CS2000-c)

Answer: A

9. As of software release PCR 7.1, what is the only Connection Control protocol supported between the

Media Gateway 15000 and its associated Gateway Controller (GWC)?

A. SIP

B. PPVM

C. ASPEN

D. H.248/MEGACO

Answer: D

10. Click the exhibit button.

How many Carrier Grade Media Gateway 15000s in the exhibit can be configured on the Multiservice Switch 15000 shelf?

Α	0	1	2	3	4	5	6	7
Ext. Slot	CP3	CP3	4p GE	4p GE	VSP 3-o	VSP 3-0	VSP 3-0	VSP 3-0
В	8	9	10	11	12	13	14	15
Ext. Slot	VSP 3-0	VSP 3-o	VSP 3-o	VSP 3-0	VSP 3-0	VSP 3-0	VSP 3-0	VSP 3-0

A. 6

B. 8

C. 14

D. 16

Answer: A