



# ITTEST

## QUESTION & ANSWER

Guías de estudio precisos, Alta tasa de paso!



Ittest ofrece información actualizada de forma gratuita en un año!

<http://www.ittest.es/>

**Exam : 9L0-606**

**Title : System Administration of  
Mac OS**

**Version : DEMO**

**1. Your umask is set to 026. You use touch from the command line to create a new file. What are the permissions on the new file?**

- A.600
- B.640
- C.644
- D.751
- E.755

**Correct: B**

**2. What three (3) pieces of information must be specified in the Active Directory plug-in configuration in order for Mac OS X v10.3 to bind to Active Directory via the Active Directory plug-in? (Choose THREE.)**

- A. IP address
- B. Computer ID
- C. Ethernet Address
- D. Active Directory Tree
- E. Active Directory Forest
- F. Active Directory Domain
- G. Active Directory Mount Point

**Correct: B E F**

**3. Which two (2) statements about passwords for local user accounts in Mac OS X v10.3 are true? (Choose TWO.)**

- A. DirectoryService is the authoritative authentication agent for crypt and shadow passwords.
- B. A crypt password can be 32 bytes in length; a shadow password has no length limitation.
- C. A crypt password is stored as a hash in the user account; a shadow password is stored as several hashes in a file.
- D. A crypt password is accessible by anyone using the computer; a shadow password is only accessible by the System Administrator (root).
- E. Mac OS X v10.3 creates crypt passwords by default; shadow passwords are created for a user account when the option is specified in System Preferences.

**Correct: C D**

**4. Which is a limitation of using lookupd -d?**

- A. The daemon, lookupd, is interactive.
- B. The results of the lookupd -d command are from a new instance of lookupd.
- C. The lookupd -d command is used to find information on DNS resolution.
- D. If configured to use DSAgent, the lookupd -d command will get the same results as DirectoryService.

**Correct: B**

**5. If a router on the Internet receives a packet destined for a private (non-routable) IP address, the router will \_\_\_\_\_.**

- A. drop the packet
- B. return the packet
- C. broadcast the packet
- D. forward the packet to the private network gateway

**Correct: A**

**6. Identify a disadvantage of supplementing Active Directory with directory services running on**

**Mac OS X Server.**

- A.A modification to the Active Directory schema is necessary.
- B.The ability to manage individual user accounts in Mac OS X is sacrificed.
- C.You can no longer manage directory services with tools provided by Apple.
- D.A configured directory on Mac OS X Server must be added to the Active Directory domain.

**Correct:B**

**7.What does the -LoginHook option do in the code sample below from /etc/ttys? console**  
**"/System/Library/CoreServices/loginwindow.app/loginwindow -PowerOffDisabled YES**  
**-LoginHook /Users/Admin/Scripts/mailLoginInfo" vt100 on secure**  
**window=/System/Library/CoreServices/WindowServer**

- A.Disables Shutdown and Restart buttons for non-administrators
- B.Invokes the script mailLoginInfo when a user logs in to the computer
- C.Sets the terminal type to vt100 for each user who logs in to the computer
- D.Starts the main windowing system, WindowServer, in a secure Console window on startup

**Correct:B**

**8.Which command will identify all files in the hierarchy rooted at the current directory that have either the setuid or the setgid bit set?**

- A.find . -perm +2000
- B.find . -perm +3000
- C.find . -perm +4000
- D.find . -perm +5000
- E.find . -perm +6000
- F.find . -perm +7000

**Correct:E**

**9.Which three (3) statements about encrypted disk images are true? (Choose THREE.)**

- A.Encrypted disk images are read-only.
- B.Encrypted disk images can be re-sized.
- C.Encrypted disk images use AES 128-bit encryption.
- D.The maximum size of encrypted disk images is 1 GB.
- E.Mac OS X does not leave any Cleartext copies of the contents of files opened from encrypted disk images.
- F.A tcpdump of network traffic relating to mounting an encrypted disk image reveals the disk image data in unencrypted form.

**Correct:B C E**