



## **QUESTION & ANSWER**

Guías de estudio precisos, Alta tasa de paso!



Ittest ofrece información actualizada de forma gratuita en un año!

http://www.ittest.es/

## Exam : E20-526

# Title: XtremIO Solutions and<br/>Design Specialist Exam for<br/>Technology Architects

## Version : DEMO

- 1. Which Multipathing software is supported by ExtremIO?
- A. PowerPatch/VE and NMP on ESXi Host
- B. MPIO on non-clustered Microsoft Windows Hosts only
- C. PowerPath/VE on Microsoft Windows VMs hosted by ESXi
- D. Native MPIO on IBM AIX clusters

#### Answer: C

2.A customer has a workload with the following attributes:

- . Generates 500.000 IOPs
- . Maximum Bandwindth of 14GB/s

Which XtremIO X2 solution should be recommended to the customer?

- A. 1 X-Brick
- B. 2 X-Brick
- C. 3 X-Brick
- D. 4 X-Brick

#### Answer: B

3.A customer wants to connect their Storage Controller to Fiber Channel switches using as many Fiber Channel port as possible.

Which port of each storage controller shown in the exhibit should be used?

- A. 1 and 2
- B. 1,2,3 and 4
- C. 2 and 3
- D. 3 and 4

#### Answer: A

4. You are connecting a Linux host to an XtremIO array. The host will be connected to the array using the Qlogic HBA's.

Based on the recommended best practice, what is the value for the queue depth?

- A. 128
- B. 256
- C. 1024
- D. 8192

#### Answer: B

5.What should the Oracle Redo Log block size be set to in order to prevent log entries from being misaligned by read-modify-write operators for an Oracle Database?

- A. 4 Kb
- B. 8 Kb
- C. 16 Kb
- D. 24 Kb

#### Answer: C