



ITTEST

QUESTION & ANSWER

Guías de estudio precisos, Alta tasa de paso!



Ittest ofrece información actualizada de forma gratuita en un año!

<http://www.ittest.es/>

Exam : **HP0-064**

Title : HP BladeSystems C-Class
Solutions 1

Version : DEMO

1.Which port on a BladeSystem c-Class enclosure serves as a service port for temporary connection to a PC?

- A.USB port
- B.serial connector
- C.enclosure link-up port
- D.enclosure link-down port

Correct:C

2.If you are installing a Gbe2c switch, how can the switch obtain an IP address remotely?

- A.through a Telnet connection on any server with access to the Internet
- B.from a BOOTP server on the network, using the switchs MAC address
- C.through a VT100 terminal emulation session on any server on the network
- D.through the switch browser-based interface (BBI) or command line interface (CLI)

Correct:B

3.In a BladeSystem c-Class enclosure, how are the interconnects connected to the device bays?

- A.CAT5 cables
- B.RJ-45 cables
- C.100-pin connectors
- D.connections are hard-wired

Correct:D

4.Which statements describe the default role of the operator access level in an HP GbE2c switch for BladeSystem c-Class? (Select two.)

- A.An operator can reset ports or the entire switch.
- B.An operator can change user and administrator passwords.
- C.Operator-level access is the default on HP GbE2c switches.
- D.An operator can make permanent changes to the switch configuration.
- E.Any configuration changes an operator makes are undone by resetting the switch.

Correct:A E

5.You want to establish a connection to the switch through the Onboard Administrator. Your workstation has a terminal application installed and a null modem serial cable connected to the Onboard Administrator module, but you are unable to connect. What is the most probable cause of the error?

- A.You have the wrong IP address.
- B.Another user is logged in to the switch.
- C.You can access the switch only through Advanced Web Tools.
- D.You can access the switch only through the application program interface (API).

Correct:B

6.You are configuring the Ethernet interconnects for a customers system. The customer is deploying a solution that maintains a 1:1 ratio between servers and switch ports. Which solution will be most cost-effective for this customer?

- A.Virtual Connect
- B.Redundant GbE2c switches
- C.HP Ethernet Pass-Thru Module
- D.HP InfiniBand 4X DDR Switch Module

Correct:C

7.Which switch should you use as the primary Fabric Configuration Server in a mixed fabric containing multiple Brocade switches?

- A.the primary switch for each zone
- B.the switch with the most available ports
- C.it does not matter which switch you use
- D.any switch with the current Fabric OS installed

Correct:D

8.To complete the installation and ensure proper cooling, which step should you take after you have installed the server blades in a BladeSystem c-Class enclosure?

- A.Install blade and fan blanks.
- B.Install redundant cooling fans.
- C.Use Thermal Logic software to restrict BTUs
- D.Activate the Insight Display and check for error messages.

Correct:A

9.You have just installed an interconnect switch in an HP BladeSystem c-Class, and the switch does not power up. What should you check first?

- A.interconnect type and location
- B.mezzanine cards are correctly installed
- C.server blade is in the correct device bay
- D.enclosure and switch status in the Onboard Administrator GUI

Correct:D

10.If you are installing a Type 1 mezzanine card in a BladeSystem c-Class enclosure, which step should you take after you have identified the target server blade in the enclosure?

- A.Back up all server data.
- B.Remove the server blade.
- C.Remove the access panel.
- D.Power down the server blade.

Correct:A