



# ITTEST

## QUESTION & ANSWER

Guías de estudio precisos, Alta tasa de paso!



Ittest ofrece información actualizada de forma gratuita en un año!

<http://www.ittest.es/>

**Exam : HP0-242**

**Title : Supporting the ESL9000**

**Version : DEMO**

**1.On which Operator Control Panel screen can you read error logs?**

- A.Overview
- B.Tapes
- C.Operator
- D.Service

**Correct:C**

**2.The Use Barcodes button on the Systest Library screen of an ESL library is activated. What occurs?**

- A.Selected cartridges are swapped during the test, based on the barcode label.
- B.Barcodes are read as cartridges are swapped.
- C.Cartridges are not swapped; barcodes are used to simulate cartridge swapping.
- D.Cartridges are returned to the previous location after the test terminates.

**Correct:B**

**3.What is the maximum number of times an HP Ultrium cleaning cartridge can be used?**

- A.5
- B.10
- C.15
- D.20

**Correct:C**

**4.What is the format of the ESL Interface Manager Command Line Interface command prompt?**

- A.CLI >
- B./ >
- C.IM >
- D. >

**Correct:B**

**5.The Interface Manager card in an ESL library connects to the Fibre Channel Interface Controllers across a \_\_\_\_.**

- A.PCI bus
- B.multimode Fibre Channel cable
- C.private Ethernet cable
- D.serial cable

**Correct:C**

**6.The Actions button on a Command View ESL screen is used to \_\_\_\_.**

- A.perform the selected action
- B.open a menu of currently available actions
- C.display information about the current action
- D.take control over the current action

**Correct:B**

**7.From which Operator Control Panel screen can you configure library options?**

- A.License
- B.Tapes
- C.Services
- D.Operator

**Correct:D**

**8.The cascade port of the Interface Manager card in an ESL library uses \_\_\_\_.**

- A.DHCP by default to acquire an IP address across the network
- B.a pre-assigned, customizable IP address
- C.no IP address by default; you must set it during the configuration process
- D.a hardcoded IP address that cannot be changed

**Correct:D**

**9.What is the default baud rate for configuring the Fibre Channel interface card though the serial connection?**

- A.9600
- B.19200
- C.57600
- D.115200

**Correct:D**

**10.Which connection type has the highest priority when connecting to a Network Storage Router (NSR) through the Interface Manager card?**

- A.Command View ESL
- B.Telnet
- C.FTP
- D.Serial

**Correct:D**