



# ITTEST

## QUESTION & ANSWER

Guías de estudio precisos, Alta tasa de paso!



Ittest ofrece información actualizada de forma gratuita en un año!

<http://www.ittest.es/>

**Exam : HP0-680**

**Title : Implementing Enterprise  
Virtual Array**

**Version : Demo**

1 .Which Compaq fault-tolerant methodology uses multiple disk controllers

- A. RAID 5
- B. multiplexing
- C. duple Xing
- D. RAID 1

Answer: C

2 .Which Compaq RAID level requires two parity drives

- A. Distributed Data guarding
- B. Dedicated Parity Drive
- C. Advanced Data Guarding
- D. Distributed Parity

Answer: C

3 .When memory is the only component to be tested, which diagnostic option should be select

- A. Quick Check
- B. Automatic
- C. Prompted
- D. CPQSET+

Answer: C

4 .What do online spares enable the server to do in the Advanced Memory Protection system

- A. fail over to the spare bank.
- B. Protect against a double bit error
- C. Read memory faster
- D. Stripe across DIMMS

Answer: A

5 .Where are the Compaq server system interlock LEDs found

- A. hot-pluggable power supply
- B. hot-pluggable backplane
- C. system IO board
- D. terminator board

Answer: C

6 .Which utility is recommended to be run after replacing a Compaq server IO device

- A. system configuration Utility
- B. ERASE Utility
- C. Insight Manager
- D. IO configuration Utility

Answer: A

7 .What IO device is used to cheek Compaq server information without using a monitor

- A. IMD
- B. UID
- C. Parallel Port
- D. USB Port

Answer: A

8 .Which PCI buses do Compaq Servers support

- A. 32 bit and 64 bit B. 32 bit and 48 bit
- C. 32 bit, 64 bit and 128 bit
- D. 64 bit and 128 bit

Answer: A

9 .What regulated the Pentium III processor power

- A. processor
- B. system board
- C. processor terminator
- D. processor terminator
- E. processor power module

Answer: D

10 .What regulates the Pentium II processor power

- A. Processor
- B. System board
- C. Processor
- D. Processor Power Module

Answer: D

11 .What new Compaq server processor technology eliminates the need for an external Processor power Module

- A. Eight-way Way Profusion Chip Set
- B. On-Chip voltage Regulation (OCVR)
- C. Symmetric Multiprocessing
- D. Asymmetric Multiprocessing

Answer: B

12 .On vraid5, the HSV110 will write one parity segment fro every \_\_\_\_\_ data segments.

- A. three
- B. four
- C. five
- D. six

Answer: B

13 .What is the minimum number of quorum disks created when the EVA is initialized

- A. two
- B. four
- C. five
- D. six

Answer: C

14 .You have a disk group with no protection set. It contains three virtual disks a vraid0, a vraid1, and a vraid5 that takes up half of the available disk space.

- A. All three Vriad0 disks will fail.
- B. The Vraid0 will fail and the Vraid 1and Vraid5 will continue to run reduced.
- C. The Vraid0 will fail and Vraid1 and Vraid5 data will be reconstructed and will continue as normal.
- D. The data from the failed disk drive will be reconstructed and all three vraid disks will continue as normal.

Answer: C

15 .Which tow EVA management function can be performed using the storage management appliance (Choose two.)

- A. configure event notification
- B. monitor performance of the EVA
- C. configure temperature thresholds
- D. enable backend device loop ports
- E. start Command View EVA service
- F. configure automatic file system backups

Answer: A,E

16 .What is used to disable a Compaq server serial port

- A. Compaq Insight Manager
- B. System Board Switch
- C. System Configuration Utility
- D. Nothing, as it is disabled by default

Answer: C

17 .In a EVA with version 2 hardware which ports are used in the IO module for supported communication with the loop switch Stretches

- A. none
- B. tope
- C. bottom
- D. all ports on IO module A and B

Answer: B

18 .Which two products are replaces by the EVA (Choose two.)

- A. VA7100
- B. VA7400
- C. Xp1024
- D. MSA1000
- E. Ema12000

Answer: B,E

19 .Compared to the size of the disk drive, how much capacity will a customer have with a Compaq RAID 1 configuration have.

- A. none
- B. 33%
- C. 50%
- D. 75%

Answer: C

20 .When is it safe to remove Hot Plug memory

- A. when the Hot plug LED is green
- B. when the Hot plug LED is red
- C. when the four bank LEDs are green
- D. when the four bank LEDs are red

Answer: A