



ITTEST

QUESTION & ANSWER

Guías de estudio precisos, Alta tasa de paso!



Ittest ofrece información actualizada de forma gratuita en un año!

<http://www.ittest.es/>

Exam : HP0-J26

**Title : Designing and Implementing
HP SAN Solutions**

Version : Demo

1.To install additional switches, you must determine the ideal ISL ratio. Which ISL ratio range is recommended for less I/O intensive application requirements (less than 70 MB/s at 2 Gb/s, less than 140 MB/s at 4 Gb/s, less than 280 MB/s at 8 Gb/s)?

- A.3:1 to 1:1
- B.1:1 to 3:1
- C.15:1 to 7:1
- D.7:1 to 15:1

Answer:B

2.Which Fibre Channel timing variables must match in an interoperable fabric?

- A.Timing variables do not need to match.
- B.R_A_TOV, E_D_TOV and B_B_TOV
- C.R_A_TOV and E_D_TOV
- D.R_A_TOV and B_B_TOV

Answer:C

3.You are preparing an installation plan for implementing a new SAN design and want to ensure all customer needs are included. Which data collection method requires that you create a process list and review all relevant stakeholders?

- A.Card Arrangement
- B.Information Extraction
- C.Brainstorming
- D.Process Mapping

Answer:B

4.Which information should be included in the topology map documentation of a SAN design provided to your support organization? (Select two.)

- A.serial numbers of connected servers
- B.SAN switch zoning configurations
- C.storage controller operating mode parameters
- D.IP addresses of the connected servers
- E.World Wide Names of all nodes and devices

Answer:B C

5.You are implementing a SAN infrastructure including an HP StorageWorks EVA4400 at a customer site. The customer is interested in using three-site cascaded replication functionality. What should you recommend to accomplish this? (Select two).

- A. HP StorageWorks FlexCopy
- B. HP Continuous Access EVA
- C. additional disks in the EVA
- D. HP Virtual Replicator
- E. HP Business Copy EVA

Answer:B E

6.Which HP tool provides the ability to create a Microsoft Visio diagram of a SAN topology for a customer documentation?

- A.SAN Health
- B.SAN Designer
- C.SAN Visibility

D.SAN Navigator

Answer:C

7.A single Fibre Channel router is implemented in an existing SAN. What can be accomplished?

- A.fabric management service
- B.fabric interconnection without merge
- C.SAN availability improvement
- D.SAN extension across long distances

Answer:B

8.Which features can affect performance in a SAN? (Select three.)

- A.cable modes
- B.number of ISLs
- C.type of LC connector
- D.storage array configuration
- E.type and capacity of disks used
- F.storage access restrictions

Answer:B D E

9.What has the most influence on the response time of a hard disk drive?

- A.arbitration
- B.host request
- C.rotational delay
- D.seek time

Answer:C

10.You are preparing for a homogeneous fabric merge and notice the customer set the same domain ID for all fabrics. What will happen if this is not corrected?

- A.Enabled zone configurations are immediately disabled.
- B.Domain IDs remain unchanged and the fabrics become segmented.
- C.Domain IDs are automatically renumbered and the fabrics merge, but port zoning is affected.
- D.Domain IDs are automatically renumbered and the fabrics merge without any side effect.

Answer:B