



# ITTEST

QUESTION & ANSWER

Guías de estudio precisos, Alta tasa de paso!



Ittest ofrece información actualizada de forma gratuita en un año!

<http://www.ittest.es/>

**Exam** : **HPE6-A75**

**Title** : Aruba Certified Edge  
Professional Exam

**Version** : DEMO

1. Which technologies can prevent split brain in a VSF fabric that includes Aruba 2930F switches?

- A. ARP MAD or OOBM MAD
- B. VLAN MAD or ARP MAD
- C. OOBM MAD or LLDP MAD
- D. LLDP MAD or VLAN MAD

**Answer: D**

2. Refer to the exhibit.

Configuration » Services » Edit - CompanyX Onboard Authorization

### Services - CompanyX Onboard Authorization

Summary	Service	Authentication	Roles	Enforcement
Use Cached Results:	<input type="checkbox"/> Use cached Roles and Posture attributes from previous sessions			
Enforcement Policy:	CompanyX Onboard Authorization Policy <span>Modify</span>			<a href="#">Add new En</a>
<b>Enforcement Policy Details</b>				
Description:	Sample policy controlling authorization during Onboard provisioning			
Default Profile:	[Deny Access Profile]			
Rules Evaluation Algorithm:	evaluate-all			
<b>Conditions</b>		<b>Enforcement Profiles</b>		
1. (Date:Day-of-Week <b>BELONGS_TO</b> Monday, Tuesday, Wednesday, Thursday, Friday, Saturday, Sunday)		[Allow Access Profile], [Aruba Terminate Session]		

Exhibit: accp67-543

Based on the configuration of the Enforcement Profiles In the Onboard Authorization service shown, which Onboarding action will occur?

- A. The device will be disconnected from the network after Onboarding so that an EAP-TLS authentication is not performed.
- B. The device will be disconnected from and reconnected to the network after Onboarding is completed.
- C. The device's onboard authorization request will be denied.
- D. The device will be disconnected after post-Onboarding EAP-TLS authentication, so a second EAP-TLS authentication is performed.
- E. After logging in on the Onboard web login page, the device will be disconnected from and reconnected to the network before Onboard begins.

**Answer: B**

3. Refer to the exhibit.

Configuration » Authentication » Sources » Add - remotelab AD

## Authentication Sources - remotelab AD

Filter Name	Attribute Name	Alias Name	Enabled As
1. Authentication	dn	UserDN	-
	department	Department	Role, Attribute
	title	Title	Attribute
	company	company	-
	memberOf	memberOf	Role, Attribute
	telephoneNumber	Phone	Attribute
	mail	Email	Attribute

Exhibit: accp67-312

Based on the Attribute configuration shown, which statement accurately describes the status of attribute values?

- A. Only the attribute values of department and memberOf can be used in role mapping policies.
- B. The attribute values of department, title, memberOf, telephoneNumber, and mail are directly applied as ClearPass.
- C. Only the attribute value of company can be used in role mapping policies, not the other attributes.
- D. The attribute values of department and memberOf are directly applied as ClearPass roles.
- E. Only the attribute values of title, telephoneNumber, and mail can be used in role mapping policies.

**Answer: D**

4. An administrator wants to use Airwave to manually add devices on the network.

Where should the administrator perform this action?

- A. in Device Setup
- B. in Groups
- C. in AMP Setup
- D. in Devices

**Answer: A**

5. Refer to the exhibit.

```
Switch-1# show link-keepalive
```

#### Status and Configuration - UniDirectional Link Detection (UDLD)

```
Keepalive Retries : 4
Keepalive Interval : 5000 ms
Keepalive Mode : forward-then-verify
```

Port	Enabled	Physical Status	Keepalive Status	Adjacent Switch	UDLD VLAN
A23	Yes	up	failure	00fd45-653ae9	untagged

Switch-1 and Switch-2 connect on interface A23. The switches experience a connectivity issue. The network administrator sees that both switches show this interface as up. The administrator sees the

output shown in the exhibit on Switch-1.

What is a typical issue that could cause this output?

- A. a hardware issue, such as a broken cable
- B. asymmetric routing introduced by a routing configuration error
- C. an issue with queuing, caused by mismatched QoS settings
- D. mismatched IP addresses on the VLAN for the link

**Answer: A**