



# ITTEST

## QUESTION & ANSWER

Guías de estudio precisos, Alta tasa de paso!



Ittest ofrece información actualizada de forma gratuita en un año!

<http://www.ittest.es/>

**Exam : JN0-363**

**Title : Service Provider Routing  
and Switching, Specialist  
(JNCIS-SP)**

**Version : DEMO**

1.Which BGP attribute Is used to detect touting loops?

- A. AS path
- B. MED
- C. local preference
- D. next hop

**Answer: A**

2.What is the correct order of BGP attributes for active route selection?

- A. next hop -> local preference -> AS path -> MED -> origin
- B. next hop -> AS path -> local preference -> origin -> MED
- C. next hop -> local preference -> AS path -> origin -> MED
- D. next hop -> origin -> local preference -> AS path -> MED

**Answer: C**

3.Which new field is added to an IPv6 header as compared lo IPv4?

- A. version
- B. checksum
- C. fragment offset
- D. flow label

**Answer: D**

4.How does a Junos device learn about MAC addresses when It is first connected to an Ethernet LAN?

- A. The device sends out a network broadcast message asking for all devices and MAC addresses on the network and stores this information In addition lo the interface from which the response was received.
- B. The device learns the destination MAC addresses from traffic in the network and stores this MAC address in addition to the interface from which the traffic was received.
- C. The device learns the source MAC addresses from traffic in the network and stores this MAC address in addition to the interface from which the traffic was received.
- D. The device sends out a network multicast message asking for all devices and MAC addresses on the network and stores this Information in addition to the interface from which the response was received.

**Answer: C**

5.Which LSA type does an OSPF ABR use to advertise external routes generated by an NSSAASBR into the backbone?

- A. Type 5
- B. Type 7
- C. Type 3
- D. Type 1

**Answer: B**